

GENSET MODEL

Model	M 2000
Mechanical version	Open version with compact base frame and modular fuel tanks.
Fuel Tank Capacity l.	0

RATED TECHNICAL DATA

Prime Power (PRP)	2000.00 kVA
Prime Power (PRP)	1600.00 kW
Emergency power (E.P.)	2200.00 kVA
Emergency power (E.P.)	1760.00 kW
Rated Power Factor (cosφ)	0.8
Windings	Three phases Series Star
Rated three-phase concatenated voltage	400 V
Rated phase-neutral voltage	230 V
Rated frequency	50 Hz
Fuel type	Diesel

DIMENSIONS AND NOISE

Length	6200 mm
Width	2005 mm
Height	2561 mm
Weight	15150 kg
Sound pressure 7 m.	- dBA

FUEL CONSUMPTION

Fuel Cons. at 100% (E.P.)	472.00 l/h
Fuel Cons. at 100% (P.R.P.)	419.00 l/h
Fuel Cons. at 75% (P.R.P.)	319.00 l/h
Fuel Cons. at 50% (P.R.P.)	226.00 l/h
Fuel Cons. at 25% (P.R.P.)	130.00 l/h

GENERAL ALTERNATOR DATA

Alternator brand	STAMFORD
Alternator model	PI734F
P.R.P. Power	2080.0 kVA
E.P. Power	2250.0 kVA
Winding	Three phases Series Star
Terminals Number	6.00 nr.
IP Protection	23
Electronic regulator	MX341
Precision	± 1.00 %



For illustrative purposes only

GENERAL ENGINE DATA

Engine brand	MITSUBISHI
Engine model	S16R-PTAA2
Cylinders	16
R.P.M.	1500
Cubic capacity	65.37
Air intake	Turbo
Standard voltage	24 Vdc
Sae	-
BMEP	2060 kPa
Cooling	Water
Flywheel P.R.P. Power	1683.7 kW
Flywheel E.P. Power	1894.7 kW
Electronic regulator	Standard
Precision class	G3
Oil quantity	230.00
Engine Antifreeze capacity	170.00
Radiator type	Temperate
Heat from radiator	536.00 kW
Heat from exhaust	1284.00 kW
Heat from radiation	124.00 kW
Exhaust temperature	0 °C
Cooling air flow	2500.00 m³/min
Combustion air flow	141.00 m³/min
Exhaust gas flow	374.00 m³/min
EU Stage	Not available

CONTROL PANELS

AMF25



STANDARD REFERENCE CONDITIONS

Standard reference conditions temperature 25°C, altitude 100m asl, relative humidity 30%, atmospheric pressure 100 kPa (1 bar), power factor 0.8 lag, balanced load - non distortional. Fuel consumption is nominal and refers to specific weight 0.850kg/l. Sound power values refer to free field conditions: the installation site may influence the values. Dimensions, weights and other specifications contained in the technical data sheet and related attachments are nominal, subject to tolerances and refer to the model with standard equipment; any optional and additional equipment/accessories can modify weight, dimensions, performance. **P.R.P. Prime Power-Continuous power at variable load:** The power that a genset can supply in continuous service at a variable load for an unlimited number of hours per year while respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer. according to ISO8528-1. The average power supplied over time and any applicable overload must be less than the percentages stated by the Manufacturer. **L.T.P. Limited-time running power-Limited power:** The maximum power that a genset can supply for a limited time respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer according to ISO 8528-1. The number of hours per year is stated by the Manufacturer. Overload is not permitted. The data contained in this document is nominal and refers to the standard equipped model and is not binding. The manufacturer reserves the right to revise the information without notice per our policy of continuous product development and improvement. **E.P. - Emergency power:** This is the maximum power that a generating set can deliver for a limited number of hours per year while complying with the maintenance frequency stipulated under the environmental conditions set by the Manufacturer. The number of hours per year is determined by the engine manufacturer. The average power output over time must be lower than the percentages set by the engine manufacturer. Overloading is not allowed.

