

GENSET MODEL

Model	C 1000 S
Mechanical version	Silenced version with galvanized steel sheet and powder-painted canopy, compact base frame, modular fuel tanks and collection basin with leak detection sensor.
Fuel Tank Capacity l.	0

RATED TECHNICAL DATA

Prime Power (PRP)	1000.00 kVA
Prime Power (PRP)	800.00 kW
Limited Power (LTP)	1100.00 kVA
Limited Power (LTP)	880.00 kW
Rated Power Factor (cosφ)	0.8
Windings	Three phases Series Star
Rated three-phase concatenated voltage	400 V
Rated phase-neutral voltage	230 V
Rated frequency	50 Hz
Fuel type	Diesel

DIMENSIONS AND NOISE

Length	8600 mm
Width	2200 mm
Height	3400 mm
Weight	12540 kg
Sound pressure 7 m.	72.0 dBA

FUEL CONSUMPTION

Fuel Cons. at 100% (L.T.P.)	228.00 l/h
Fuel Cons. at 100% (P.R.P.)	209.00 l/h
Fuel Cons. at 75% (P.R.P.)	161.00 l/h
Fuel Cons. at 50% (P.R.P.)	113.00 l/h
Fuel Cons. at 25% (P.R.P.)	65.00 l/h

GENERAL ALTERNATOR DATA

Alternator brand	STAMFORD
Alternator model	HCI6J
P.R.P. Power	1030.0 kVA
L.T.P. Power	1110.0 kVA
Winding	Three phases Series Star
Terminals Number	12.00 nr.
IP Protection	23
Electronic regulator	MX322
Precision	± 0.50 %



For illustrative purposes only

GENERAL ENGINE DATA

Engine brand	CUMMINS
Engine model	KTA38-G5
Cylinders	12
R.P.M.	1500
Cubic capacity	37.80
Air intake	Turbo
Standard voltage	24 Vdc
Sae	-
BMEP	1868 kPa
Cooling	Water
Flywheel P.R.P. Power	857 kW
Flywheel Stand-by Power	947 kW
Electronic regulator	Standard
Precision class	G3
Oil quantity	135.00
Engine Antifreeze capacity	124.00
Radiator type	Tropicalized
Heat from radiator	594.00 kW
Heat from exhaust	590.00 kW
Heat from radiation	137.00 kW
Exhaust temperature	513 °C
Cooling air flow	1134.00 m³/min
Combustion air flow	72.80 m³/min
Exhaust gas flow	198.40 m³/min
EU Stage	Not available

CONTROL PANELS

AMF25



STANDARD REFERENCE CONDITIONS

Standard reference conditions temperature 25°C, altitude 100m asl, relative humidity 30%, atmospheric pressure 100 kPa (1 bar), power factor 0.8 lag, balanced load - non distortional. Fuel consumption is nominal and refers to specific weight 0.850kg/l. Sound power values refer to free field conditions: the installation site may influence the values. Dimensions, weights and other specifications contained in the technical data sheet and related attachments are nominal, subject to tolerances and refer to the model with standard equipment; any optional and additional equipment/accessories can modify weight, dimensions, performance. **P.R.P. Prime Power-Continuous power at variable load:** The power that a genset can supply in continuous service at a variable load for an unlimited number of hours per year while respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer. according to ISO8528-1. The average power supplied over time and any applicable overload must be less than the percentages stated by the Manufacturer. **L.T.P. Limited-time running power-Limited power:** The maximum power that a genset can supply for a limited time respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer according to ISO 8528-1. The number of hours per year is stated by the Manufacturer. Overload is not permitted. The data contained in this document is nominal and refers to the standard equipped model and is not binding. The manufacturer reserves the right to revise the information without notice per our policy of continuous product development and improvement.