

GENSET MODEL

Model **V 350 S**

Mechanical version Silenced version with galvanized steel sheet and powder-painted canopy, compact base frame, modular fuel tank and collection basin without leak detection sensor (available as optional).

Fuel Tank Capacity l. 400

RATED TECHNICAL DATA

Prime Power (PRP) 352.00 kVA

Prime Power (PRP) 281.60 kW

Emergency power (E.P.) 387.00 kVA

Emergency power (E.P.) 309.60 kW

Rated Power Factor (cosφ) 0.8

Windings Three phases Series Star

Rated three-phase concatenated voltage 400 V

Rated phase-neutral voltage 230 V

Rated frequency 50 Hz

Fuel type Diesel

DIMENSIONS AND NOISE

Length 4000 mm

Width 1295 mm

Height 2420 mm

Weight 4280 kg

Sound pressure 7 m. 70.0 dBA

FUEL CONSUMPTION

Fuel Cons. at 100% (E.P.) 75.70 l/h

Fuel Cons. at 100% (P.R.P.) 68.90 l/h

Fuel Cons. at 75% (P.R.P.) 52.20 l/h

Fuel Cons. at 50% (P.R.P.) 36.30 l/h

Fuel Cons. at 25% (P.R.P.) 20.20 l/h

GENERAL ALTERNATOR DATA

Alternator brand STAMFORD

Alternator model S4L1D-E

P.R.P. Power 360.0 kVA

E.P. Power 415.0 kVA

Winding Three phases Series Star

Terminals Number 12.00 nr.

IP Protection 23

Electronic regulator AS440

Precision ± 1.00 %



For illustrative purposes only

GENERAL ENGINE DATA

Engine brand VOLVO-PENTA

Engine model TAD1342GE

Cylinders 6

R.P.M. 1500

Cubic capacity 12.78

Air intake Turbo

Standard voltage 24 Vdc

Sae -

BMEP 2000 kPa

Cooling Water

Flywheel P.R.P. Power 303 kW

Flywheel E.P. Power 333 kW

Electronic regulator Standard

Precision class G3

Oil quantity 36.00

Engine Antifreeze capacity 0.00

Radiator type Tropicalized

Heat from radiator 134.00 kW

Heat from exhaust 195.00 kW

Heat from radiation 0.00 kW

Exhaust temperature 395 °C

Cooling air flow 0.00 m³/min

Combustion air flow 24.60 m³/min

Exhaust gas flow 0.00 m³/min

EU Stage STAGE 2

CONTROL PANELS

AMF25



STANDARD REFERENCE CONDITIONS

Standard reference conditions temperature 25°C, altitude 100m asl, relative humidity 30%, atmospheric pressure 100 kPa (1 bar), power factor 0.8 lag, balanced load - non distortional. Fuel consumption is nominal and refers to specific weight 0.850kg/l. Sound power values refer to free field conditions: the installation site may influence the values. Dimensions, weights and other specifications contained in the technical data sheet and related attachments are nominal, subject to tolerances and refer to the model with standard equipment; any optional and additional equipment/accessories can modify weight, dimensions, performance. **P.R.P. Prime Power-Continuous power at variable load:** The power that a genset can supply in continuous service at a variable load for an unlimited number of hours per year while respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer. according to ISO8528-1. The average power supplied over time and any applicable overload must be less than the percentages stated by the Manufacturer. **L.T.P. Limited-time running power-Limited power:** The maximum power that a genset can supply for a limited time respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer according to ISO 8528-1. The number of hours per year is stated by the Manufacturer. Overload is not permitted. The data contained in this document is nominal and refers to the standard equipped model and is not binding. The manufacturer reserves the right to revise the information without notice per our policy of continuous product development and improvement. **E.P. - Emergency power:** This is the maximum power that a generating set can deliver for a limited number of hours per year while complying with the maintenance frequency stipulated under the environmental conditions set by the Manufacturer. The number of hours per year is determined by the engine manufacturer. The average power output over time must be lower than the percentages set by the engine manufacturer. Overloading is not allowed.

