

GENSET MODEL

Model	P 730
Mechanical version	Open version with compact base frame and high capacity integrated fuel tank without collection basin.
Fuel Tank Capacity l.	1780

RATED TECHNICAL DATA

Prime Power (PRP)	750.00 kVA
Prime Power (PRP)	600.00 kW
Limited Power (LTP)	825.00 kVA
Limited Power (LTP)	660.00 kW
Rated Power Factor (cosφ)	0.8
Windings	Three phases Parallel Star
Rated three-phase concatenated voltage	208 V
Rated phase-neutral voltage	120 V
Rated frequency	60 Hz
Fuel type	Diesel

DIMENSIONS AND NOISE

Length	3960 mm
Width	1890 mm
Height	2300 mm
Weight	6620 kg
Sound pressure 7 m.	- dBA

FUEL CONSUMPTION

Fuel Cons. at 100% (L.T.P.)	199.00 l/h
Fuel Cons. at 100% (P.R.P.)	177.00 l/h
Fuel Cons. at 75% (P.R.P.)	129.00 l/h
Fuel Cons. at 50% (P.R.P.)	90.00 l/h
Fuel Cons. at 25% (P.R.P.)	0.00 l/h

GENERAL ALTERNATOR DATA

Alternator brand	STAMFORD
Alternator model	S6L1D-C
P.R.P. Power	875.0 kVA
L.T.P. Power	950.0 kVA
Winding	Three phases Parallel Star
Terminals Number	12.00 nr.
IP Protection	23
Electronic regulator	MX322
Precision	± 0.50 %



For illustrative purposes only

GENERAL ENGINE DATA

Engine brand	PERKINS
Engine model	4006-23TAG2A
Cylinders	6
R.P.M.	1800
Cubic capacity	22.92
Air intake	Turbo
Standard voltage	24 Vdc
Sae	-
BMEP	1977 kPa
Cooling	Water
Flywheel P.R.P. Power	638 kW
Flywheel Stand-by Power	702 kW
Electronic regulator	Standard
Precision class	G3
Oil quantity	122.70
Engine Antifreeze capacity	51.00
Radiator type	Tropicalized
Heat from radiator	498.00 kW
Heat from exhaust	695.00 kW
Heat from radiation	81.00 kW
Exhaust temperature	430 °C
Cooling air flow	1320.00 m³/min
Combustion air flow	73.00 m³/min
Exhaust gas flow	190.00 m³/min
EU Stage	Not available

CONTROL PANELS

AMF25



STANDARD REFERENCE CONDITIONS

Standard reference conditions temperature 25°C, altitude 100m asl, relative humidity 30%, atmospheric pressure 100 kPa (1 bar), power factor 0.8 lag, balanced load - non distortional. Fuel consumption is nominal and refers to specific weight 0.850kg/l. Sound power values refer to free field conditions: the installation site may influence the values. Dimensions, weights and other specifications contained in the technical data sheet and related attachments are nominal, subject to tolerances and refer to the model with standard equipment; any optional and additional equipment/accessories can modify weight, dimensions, performance. **P.R.P. Prime Power-Continuous power at variable load:** The power that a genset can supply in continuous service at a variable load for an unlimited number of hours per year while respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer. according to ISO8528-1. The average power supplied over time and any applicable overload must be less than the percentages stated by the Manufacturer. **L.T.P. Limited-time running power-Limited power:** The maximum power that a genset can supply for a limited time respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer according to ISO 8528-1. The number of hours per year is stated by the Manufacturer. Overload is not permitted. The data contained in this document is nominal and refers to the standard equipped model and is not binding. The manufacturer reserves the right to revise the information without notice per our policy of continuous product development and improvement.